

1AD2

Half-Wave Vacuum Rectifier

ELECTRICAL

Bogey Values

Filament (Coated) Voltage, AC or DC	1.25 V
Filament Current	0.2 A
Direct Interelectrode Capacitance (Approx.) Without external shield	
Plate to filament.	1.6 pF

MECHANICAL

Operating Position	Any
Type of Cathode.	Coated Filament
Maximum Overall Length	3.125 in
Seated Length.	2.500 to 2.750 in
Diameter	1.062 to 1.188 in
Dimensional Outline (JEDEC No.9-98).	See General Section
Envelope	JEDEC T9
Caps (Alternates)	

Small (JEDEC No.C1-1)

Small with Tubular Support (JEDEC No.C1-34)

Base Small-Button Duodecar 12-Pin (JEDEC No.E12-70)

TERMINAL DIAGRAM (Bottom View)

Pin 1 - Filament, Internal Shield

Pin 2 - Do Not Use^a

Pin 3 - Do Not Use^a

Pin 4 - See Note

Pin 5 - Do Not Use^a

Pin 6 - Same as Pin 1

Pin 7 - Do Not Use^a

Pin 8 - Do Not Use^a


Pin 9 - Do Not Use^a

Pin 10 - See Note

Pin 11 - Do Not Use^a

Pin 12 - Filament

Cap - Plate



Note: May be used only under conditions specified in Operating Considerations.

PULSED-RECTIFIER SERVICE

Design-Maximum Ratings

For operation in a 525-line, 30-frame system

Inverse Plate Voltage

Total dc and peak ^b	26000 V
DC	22000 V

Peak Plate Current 50 mA

Average Plate Current. 0.5 mA

Filament Voltage, AC or DC 1.05 to 1.45 V

Characteristics, Instantaneous Value

Tube Voltage Drop for plate mA = 7 225 V

^a Socket terminals 2, 3, 5, 7, 8, 9, and 11 should not be used as tie points.

^b This rating is applicable when the duration of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

← Indicates a change.



RADIO CORPORATION OF AMERICA
Electronic Components and Devices

Harrison, N. J.

DATA
6-66

1AD2

OPERATING CONSIDERATIONS

Socket Connections. Socket terminals 4 and 10 may be used as tie points for components at or near the cathode potential; otherwise, do not use.

The high voltages at which the 1AD2 is operated are very dangerous. Great care should be taken in the design of equipment to prevent the operator from coming in contact with these high voltages. Particular care against fatal shock should be taken in the measurement of filament voltage. Under all circumstances, circuit parts which may be at high potentials should be enclosed or adequately insulated.

X-Radiation. The voltages employed in some television receivers and other high-voltage equipment are sufficiently high that high-voltage rectifier tubes may produce *X-radiation* which can constitute a health hazard unless such tubes are adequately shielded. Relatively simple shielding should prove adequate, but the need for this precaution should be considered in equipment design.

